

A32FLP_{LUS} , A103FLP_{LUS} , A174FLP_{LUS}



*** version with mounted arm
(OPTIONAL)**

TECHNICAL FEATURES:

- Machine body Ø560mm
- Fan ventilator with three phase motor asynchronous
- Electric cable 9m long with industrial plug 3 Ph+ Earth 16A
- Side manual filter shaker
- Star filter of polyester cat. "L"- Ø560mm
- Inlet Ø150mm and Ø200mm
- Ø560mm waste bin with various capacities with integrated handle and wheels
- Painted version with trolley Ral 9005 (black), waste bin and filter chamber Ral 7001 (grey)
- X1 version with waste bin in stainless steel
- X2 version with waste bin and filter chamber in stainless steel
- Optional vacuum arm kit

		A32FLP	A103FLP	A174FLP
Tension / Voltage	Volts	3~ 230-400V/50Hz	3~ 230-400V/50Hz	3~ 230-400V/50Hz
Plug	A	3P + T 16A	3P + T 16A	3P + T 16A
Power	kW	2.2	3	4
Depression max	mbar max	35	30	45
Max working depression	mbar	35	30	45
Max air flow	m ³ /h	1500	3000	2500
Primary filter surface	m ²	4,2	3,2	3,2
Absolute filter surface	m ²	20	20	20
Container capacity	Lt	39	100	175
Product inlet	mm	Ø150	Ø150	Ø150
Noise level	DbA	79	79	79
Overall dimensions	cm	65x90x185h	73x110x210h	73x125x240h
Weight	Kg	92	230	235
Protection	IP	55	55	55