

A1256K, A1556, A1856K



TECHNICAL FEATURES:

- Side channel blower with three phase motor asynchronous, put into a protective housing in the back side of the vacuum cleaner.
- Electric cable 10m long with industrial plug 3Ph+T 32A that can be disconnected from the machine
- Star filter Ø560 with big filtering surface
- Manual filter shaker on top of the filter chamber
- Vacuum gauge to monitor the filter efficiency
- Container of 175l on castors with side handles for the emptying and as an option the kit lifting system to have it up with a fork lift
- Quick inlet Ø100
- Fixed wheels Ø200 and revolving wheels Ø200 with brake on bearings to grant high manoeuvrability
- Painted version with frame RAL 9005 (black) and machine Ral 7001 (grey)
- X1 version with container in stainless steel
- X2 version with container and filter chamber in stainless steel
- X3 version all in stainless steel
- Electric switchboard with soft-start and PLC to control the motor, already configured for remote control

| | | A1256K | A1556 | A1856K |
|------------------------------------|----------|----------------|----------------|----------------|
| Tension/ Voltage | Volts | 3~ 400V/50Hz * | 3~ 400V/50Hz * | 3~ 400V/50Hz * |
| Plug | A | 3P + T 32A | 3P + T 32A | 3P + T 32A |
| Power | Kw | 8.5 | 11 | 12.5 |
| Depression Max | mbar max | 360 | 520 | 360 |
| Max working depression | mbar | 220 | 450 | 290 |
| Max air flow | m³/h | 1.050 | 520 | 1.050 |
| Primary filter surface | m² | 3,4 -Ø560 | 3,4 -Ø560 | 3,4 -Ø560 |
| Upstream absolute filter surface | m² | NO | NO | NO |
| Downstream absolute filter surface | m² | 18 | 7,25 | 18 |
| Cartridge filter surface | m² | 10 | 10 | 10 |
| Container capacity | Lt | 175 | 175 | 175 |
| Product inlet | mm | Ø100 | Ø100 | Ø100 |
| Noise level | DbA | 76 | 76 | 76 |
| Overall dimensions | cm | 74x157x187h | 74x157x187h | 74x157x187h |
| Weight | Kg | 380 | 400 | 380 |
| Protection | IP | 55 | 55 | 55 |

* other voltages and frequencies available on request