

## A21P<sub>LUS</sub> MINX1.3D



### TECHNICAL FEATURES:

- Machine body Ø360mm
- Side channel turbine with single-phase asynchronous motor marked ATEX EX II 3D
- Vacuum gauge for filter clogging level indication
- 10mt power cable with industrial plug 2P+E 16A IP67 marked atex
- Manual side filter shaker
- Primary coalescing filter for vapour abatement
- Ø50mm quick coupling
- Standard limiting valve
- 25 litre container with integrated handle and wheels and special system for liquid inertisation
- Rear wheels Ø125mm, front wheels Ø100mm with brake, in antistatic version
- Standard version with frame Ral 9005 black, stainless steel container and side Ral 9003 white

A21P MINX1.3D		
Tension /Voltage	Volts	1~ 230V/50Hz
Plug	A	2P + T 16A IP67
Power	kW	1.5
Depression max	mbar	250
Max air flow	m <sup>3</sup> /h	220
Primary filtering surface	m <sup>2</sup>	1,14
Absolute filtering surface	m <sup>2</sup>	1,20
Container capacity	Lt	25
Product inlet	mm	Ø50
Noise level	dB(A)	67
Overall dimensions	Cm	47X61X135h
Weight	Kg	60
Protection	IP	65
EX Marking	EX	II3D T135 °C