

A3078, A3080KC



TECHNICAL FEATURES:

- Side channel blower with three phase motor asynchronous put into protective housing in the back side of the vacuum cleaner
- Star filter with electric filter shaker (for model A3078)
- Self cleaning system of the cartridges with compressed air (for model A3080KC)
- Vacuum gauge to control the efficiency of the filters
- Container of 175l - Ø780/560 on castors complete with side handles for the emptying and as option the lifting system to have it up with the fork lift
- Tangential inlet Ø120
- Accessories compartment put in as standard
- Painted version with frame RAL 9005 (black) and machine Ral 7001 (grey)
- X1 version with container in stainless steel
- Fast-moving wheels made of cast iron and polyurethane Ø200mm fixed and revolving with brake

		A3078	A3080KC
Tension/ Voltage	Volts	3~ 400V/50Hz *	3~ 400V/50Hz *
Plug	A	3P + T 32A	3P + T 32A
Power	Kw	20	20
Depression max	mbar max	600	320
Max working depression	mbar	440	250
Max air flow	m ³ /h	1100	2.350
Primary filter surface	m ²	4,5 - Ø780	15 - Ø780
Upstream absolute filter	m ²	NO	NO
Downstream absolute filter	m ²	34	34
Container capacity	Lt	175	175
Product inlet	mm	Ø120	Ø120
Noise level	DbA	78	76
Overall dimensions	cm	89x175x240h	89x175x240h
Weight	Kg	520	520
Protection	IP	55	55

* other voltages and frequencies available on request