

# A336



**TECHNICAL FEATURES:**

- Side channel blower with three phase asynchronous motor, put into a housing
- Electric cable 10m long with industrial plug 3Ph+ T 16A
- Vacuum meter to check the filter efficiency
- Machine body Ø460mm
- Manual filter shaker on top
- Star filter in polyester cat.“L”
- Quick inlet Ø70mm
- 48 l. dust bin with handles, removable
- Rear castors Ø125mm, front castors Ø100mm with brake

- Painted version with frame, waste bin and filter chamber Ral 9003 (white)
- X1 version with waste bin instalaess steel
- X2 version with waste bin and container in stainless steel
- X3 version with waste bin, filter chamber and fram in stainless steel

		<b>A336</b>
Tension / Voltage	Volts	230-400V/50Hz
Power	Kw	2.2
Max depression	mbar max	310
Max working depression	mbar	200
Max air Flow	m <sup>3</sup> /h	310
Primary filter surface	m <sup>2</sup>	1,90
Upstream absolute filter	m <sup>2</sup>	2,2
Downstream absolute filter	m <sup>2</sup>	4,8
Cartridge filter kit	m <sup>2</sup>	5
Container capacity	Lt	48
Product inlet	mm	Ø70
Noise level	DbA	73
Overall dimensions	Cm	50X80X154h
Weight	Kg	120
Protection	IP	55