

A346/60EPINX1.3D



TECHNICAL FEATURES:

- Machine body Ø460mm
- Side channel turbine with three-phase asynchronous motor in ATEX EX II 3D ATEX EX II 3D version positioned inside a housing at the fairing at the rear of the machine, with ABS casing
- Power supply cable 10mt with industrial plug 3Ph+T 16A - IP 67
- Manual filter shaker in upper position for cleaning the filter
- Ø70mm quick coupling
- 25 litre container with integrated handle and wheels and special system for liquid inertisation
- Drain tap located on the tank on wheels
- Rear wheels Ø125mm, front wheels Ø100mm with brake, in antistatic version
- Standard version with stainless steel container, side and fairing painted Ral 7001 grey

A346/60EPINX1.3D		
Tension /Voltage	Volts	3~ 400V/50Hz
Plug	A	3P + T 16A IP67
Power	kW	3.4
Depression max	mbar	300
Max air flow	m ³ /h	310
Primary filtering surface	m ²	1,9
Absolute filtering surface	m ²	3,1
Liquid capacity	Lt	60
Dust capacity	Lt	25
Product inlet	mm	Ø70
Noise level	dB(A)	75
Overall dimensions	Cm	64X112X155h
Weight	Kg	160
Protection	IP	55
EX Marking	EX	Ex II 2/3D H T.135 °C