

A546KECOC, A546KECOC.1



TECHNICAL FEATURES:

- Side channel blower with three phase motor asynchronous, placed into a protective housing in the back side of the vacuum cleaner
- Power cable 10mt with industrial plug 3Ph+T 16A
- Vacuum-meter to control the filter efficiency
- Ø460mm cartridge kit with 3 cartridges and total filtering surface area of 5m²
- Automatic compressed air cleaning in counter current
- 100lt container with wheels and side handles for emptying
- Quick inlet Ø70 for easy attachment of accessories
- Painted version Ral 7001 (grey)
- Fixed wheels Ø150mm and revolving wheels with brake Ø125mm

| | | A546KECOC | A546KECOC.1 |
|----------------------------------|-------------------|----------------|----------------|
| Tension/voltage | Volts | 3~ 400V/50Hz * | 3~ 400V/50Hz * |
| Plug | A | 3P + T 16A | 3P + T 16A |
| Power | kW | 4 | 5.5 (4 + 1.5) |
| Depression max | mbar | 280 | 280 |
| Max working depression | mbar | 200 | 200 |
| Max air flow | m ³ /h | 550 | 550 |
| Primary filter surface | m ² | 5 | 5 |
| Upstream absolute filter surface | m ² | NO | NO |
| Container capacity | Lt | 100 | 100 |
| Product inlet | mm | Ø70 | Ø70 |
| Noise level | DbA | 76 | 83 |
| Overall dimensions | cm | 65x110x152h | 65x110x152h |
| Weight | Kg | 135 | 145 |
| Protection | IP | 54 | 54 |

* other voltages and frequencies available on request