

## AS1556X.3D, AS356X.3D



### TECHNICAL FEATURES:

- Side channel blower with asynchronous motor, three phase, located at the bottom under the container. Marked ATEX EX II 3D
- Machine body Ø560mm
- Electric cable 10m long with industrial plug 3Ph+ earth 16A IP67
- Nylon filter bag antistatic to collect the product
- Inspection window on the cover to check the filter bag
- Relief valve put in as standard
- Straight inlet Ø70
- Container of 150 l in stainless steel
- Wheels Ø63mm with brake, antistatic version

		AS1556X.3D	AS356X.3D
Tension/ Voltage	Volts	3~230-400V/50Hz	3~230-400V/50Hz
Plug	A	3P + T 16A IP67	3P + T 16A IP67
Power	Kw	2.2	2.2
Depression max	mbar max	300	300
Max working depression	mbar	200	200
Max air flow	m <sup>3</sup> /h	210	310
Primary filter surface	m <sup>2</sup>	NO	NO
Upstream absolute filter	m <sup>2</sup>	NO	NO
Downstream absolute filter	m <sup>2</sup>	1,3	1,3
Cartridge filter surface	m <sup>2</sup>	NO	NO
Container capacity	Lt	150	150
Product inlet	mm	Ø70	Ø70
Noise level	DbA	70	73
Overall dimensions	Cm	Ø56X116H	Ø56X116H
Weight	Kg	60	72
Protection	IP	55	55
EX Marking	EX	II3D T125 °C	II3D T125 °C