

ONE32ECO, ONE63ECO, ONE103ECO



TECHNICAL FEATURES:

- Machine body Ø460mm
- Single phase brush motors double stage by-pass
- Motor-head entirely made of metal black painted
- Independent switches for each motor
- Vacuum-meter and red light to control filter efficiency
- Electric cable 9m long with Schuko plug
- Manual filter shaler on top of the head
- Star filter of polyester cat. "L"- Ø460mm
- Quick product inlet Ø70mm
- Waste bin of 39, 65 and 100 l with integrated handle and castors
- Rear castors Ø150mm, front castors Ø125mm with brake
- Painted version with trolley Ral 9005 (black), waste bin and filter chamber Ral 7001 (grey)
- X1 version with waste bin in stainless steel
- We recommend using accessories of Ø40mm and Ø50mm

		ONE32ECO	ONE63ECO	ONE103ECO
Tension /Voltage	Volts	1~ 230V/50-60Hz	1~ 230V/50-60Hz	1~ 230V/50-60Hz
Plug	A	Schuko	Schuko	Schuko
Power	Watt	2200	3300	3300
Depression max	mbar	210	210	210
Max air flow	m ³ /h	340	510	510
Primary filter surface	m ²	1,90	1,90	1,90
Absolute filter surface	m ²	3,1	3,1	3,1
Container capacity	Lt	39	65	100
Product inlet	mm	Ø70	Ø70	Ø70
Noise level	DbA	75	77	75
Overall dimensions	cm	78x64x121h	78x64x135h	78x64x155h
Weight	Kg	53	57	62
Protection	IP	43	43	43